

## 1 Description:

SketchPaint Primer is a white, insulating and quick-drying water-based adhesive primer for indoor and outdoor use. SketchPaint Primer is based on an acrylate resin with pigments and additives. It is quick-drying, flexible and insulating. In addition, it has good filling and hiding properties and forms a closed, well-adhering paint film. SketchPaint Primer is paintable with most water-based and solvent-based decorative paints. It is extremely suitable as a primer for Paint For Pro's SketchPaint.

Meets health and safety requirements for professional indoor use.

## 2 Equipment:

SketchPaint Primer can be applied with a brush, roller or air spray. When using airless spray equipment: Nozzle: 0.011 - 0.013 inch/Pressure: 150 - 200 bar and possibly dilute with water. Clean used tools with water.

## 3 Substrate:

The substrate must be clean, dry and load-bearing. Degrease where necessary. Lightly sand old paint layers to ensure optimal adhesion. SketchPaint Primer adheres to metal and smooth hard surfaces, seals porous surfaces and insulates stains.

## 4 Theoretical consumption:

Approx. 10 m<sup>2</sup>/L per layer. Depending on many factors such as porosity and roughness of the substrate and material loss during application.

## 5 Application instructions:

- Do not process at temperatures below +5 ° C and/or a relative humidity of more than 80%.
- Pre-treat the substrate properly.
- Before use, the product must be intensively stirred to a good homogeneity.
- Preferably use undiluted when applied with roller or brush.
- Dilute with water if necessary with spray application.
- Tack-free after about 30 minutes.
- After about 2 hours of drying time, overcoat with SketchPaint.

# SketchPaint Primer – Technical Data Sheet



MagPaint Europe BV  
Riezenweg 2  
NL-7071 PR Uift

## 6 Storage conditions:

In unopened packaging, in a dry, well-ventilated room, away from direct sunlight at temperatures between 5°C and 35°C.

## 7 VOC/Certification:

EU limit value for this product (2004/42/EC, Cat. GWB, 2010): 30 g/L. This product contains a maximum of 30 g/L VOC.

## 8 Specifications:

<b>Commodity code:</b>	320910.
<b>Colour:</b>	White
<b>Sheen:</b>	Satin gloss
<b>Density:</b>	1.2 - 1.3 kg/L.
<b>Layer thickness:</b>	Approx. 40 µ for one layer.
<b>Theoretical consumption:</b>	Approx. 10 m <sup>2</sup> /L, depending on the substrate and application method.
<b>Viscosity:</b>	Ready to use. Dilute with water if necessary.
<b>VOC:</b>	EU limit value for this product (2004/42/EC, Cat. GWB, 2010): 30 g/L. This product contains a maximum of 30 g/L VOC.
<b>Processing</b>	T: > +5 ° C RH: <80%.
<b>Tack-free:</b>	Approx. 30 minutes at 20 ° C and 65% RHV
<b>Ready to use:</b>	Approx. 2 hours at 20 ° C and 65% RH
<b>Units:</b>	0.5 litres - 1 litre - 2.5 litres.
<b>Shelf life:</b>	At least 24 months under the right storage conditions.