SAFETY DATA SHEET

Date of issue: 26 February 2018 BlackboardPaint Trade name:

Page: 1/11 Version: 3.2



SECTION 1: Identification of the substance/mixture and of the company/undertaking.

1.1 Product identifier

BlackboardPaint (black, blue, green, pink, lime, Trade name:

gray, red)

SchultafelFarbe - SchoolbordVerf Synonyms:

1.2 Relevant identified uses of the substance or mixture and uses advised

against: Paint For Pros BlackboardPaint is a water-based paint for walls and

school boards made of wood or metal. Or for other materials

that have been pre-treated with a suitable primer.

Paint for Pros BlackboardPaint can be written on using all common types of chalk, except oil-based chalk. For indoor use

only.

Product category: PROC19 (Hand-mixing),

PROC10 (Roller application or brushing).

1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier: MagPaint Europe B.V.

Riezenweg 2 7071 PR Ulft

THE NETHERLANDS +31 (0) 315 38 64 73

Fax: +31 (0) 315 74 52 00 Email: info@magpaint.com Website: www.magpaint.com

Further information obtainable from:

Tel.:

Contact person: Mike Poorthuis +31 (0) 315 38 64 73 Tel.: info@magpaint.com Email:

Working hours (business days): 09h00-17h00

1.4. Emergency telephone number

The Netherlands: National Poison Information Centre: +31 (0) 30 247 88 88 Belgium: Belgian Poison Centre: +32 (0) 70 245 245 United Kingdom: UWIC: +44 (0) 29 204 16388

SECTION 2: Hazards identification.

2.1. Classification of the substance or mixture

Classification in accordance with Regulation (EC) no 1272/2008: Void.

2.2. Label elements

In accordance with Globally Harmonized System, EU (GHS)

Hazard pictograms: Signal word: Hazard statements:

MagPaint Europe B.V. Riezenweg 2

NL - 7071 PR UIft

SAFETY DATA SHEET

Date of issue: 26 February 2018 BlackboardPaint Trade name:

Page: 2/11 Version: 3.2

EUH208 Contains mixture of: 5-Chloro-2-Methyl-2H-Isothiazol-3-one and

2-Methyl-2Hisothiazol-3-one (3:1). May produce an allergic

reaction.

Precautions:

Hazard-determining components for

labelling:

2.3. Other hazards

Results of PBT and vPvB assessment

PBT No. vPvB No.

SECTION 3: Composition/information on ingredients.

3.1. Substances Not applicable.

3.2. Mixtures

Chemical description: Preparation comprising the following component(s), water base

and (other) unclassified components.

Mixture of: 5-Chloro-2-Methyl-2H-Isothiazol-3-one and 2-Methyl-2Hisothiazol-3-one (3:1)

CAS#: 55965-84-9

EC#: Mixture of: 5- Chloro-2-Methyl-2H-Isothiazol-3-one and 2-

Methyl-2Hisothiazol-3-one (EC# 220-239-6) (3:1)

Index#: 613-167-00-5

REACH reg.#:

Content (W/W): < 0.0015 %

Danger, 1272/2008/EC: Acute Tox. 3; H301, H311, H331 - Skin Corr.1B; H314 -

Skin Sens. 1; H317 - Aquatic Acute 1; H400 -

Aquatic Chronic 1; H410 Specific classification limits, Note:

- Skin Corr. 1B; H314: C ≥ 0.6 %;

- Skin Irrit. 2; H315: $0.06 \% \le C < 0.6 \%$; - Eye Irrit. 2; H319: $0.06 \% \le C < 0.6 \%$;

- Skin Sens. 1; H317: C ≥ 0.0015 %.

Full text of H- and EUH-phrase(s): see section 16.

SECTION 4: First aid measures.

4.1. Description of first aid measures

General information:

If in doubt or if symptoms persist, seek medical attention. Eye contact:

Mild irritation. Flush eyes thoroughly with water (for at least 10 minutes) while holding eyelids open. Then immediately consult

a physician/ophthalmologist.



PAINT FOR PROS

SAFETY DATA SHEET

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 3/11 Version: 3.2

Skin contact: Remove mechanically, wash with plenty of soap and water,

liberally apply skin cream to clean skin. Consult a physician in

case of persistent pain or redness.

Ingestion: Have person rinse mouth thoroughly with water, and then spit

out rinse water. Never make an unconscious person drink fluids

because of risk of suffocation. Do NOT induce vomiting. If

symptoms develop: Get medical advice/attention

If aerosol or vapour is inhaled

in high concentrations: Take the person into the fresh air, keep him warm, let him rest.

If symptoms occur (e.g. breathing difficulties) medical attention

is required.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: No known significant effects or critical hazards.

Sanding dust of reacted material may cause irritation of

respiratory tract.

Skin contact: By mechanical damage (particles): redness.

Eye contact: By mechanical damage (particles): irritation, redness and pain.

Ingestion: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Further medical treatment: Symptomatic treatment and supportive therapy as prescribed.

SECTION 5: Firefighting measures.

5.1. Extinguishing media

Suitable extinguishing media: Use CO2, ABC powder. Fight larger fires with water spray.

Unsuitable extinguishing media for safety reasons: A direct water jet may be ineffective.

5.2. Special hazards arising from the substance or mixture

Special hazards: Not classified as flammable. In case of fire, hazardous and toxic

vapours may be released. Possible decomposition products are:

carbon monoxide and carbon dioxide.

5.3. Advice for fire fighters

Protection of fire-fighters: For fire-fighters, mouth and nose protection with independent air

supply (breathing apparatus) and full (chemical) protective clothing are mandatory. Use qualified personnel who are well aware of the dangers of this product. Clean the equipment thoroughly after use (shower, clean clothing thoroughly and

check suitability).

Additional information: If closed containers are exposed to fire, keep cool with water. In

a fire or if heated, a pressure increase will occur and the

container may burst.

SECTION 6: Accidental release measures.

6.1. Personal precautions, protective equipment and

emergency procedures Wear appropriate personal protective equipment, including

safety glasses, personal protective clothing and chemical

PAINT FOR PROS

SAFETY DATA SHEET

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 4/11 Version: 3.2

resistant gloves when cleaning up major spillages. Ventilate the

area.

6.2. Environmental precautions Prevent product from entering sewers or surface water. If

significant quantities are being released in the environment, inform the local authorities. Do not allow to enter the soil or

subsoil.

6.3. Methods and material for containment and

cleaning up Contain and collect spillages with non-combustible absorbent

materials e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. Wash the spillage area clean with

water and detergent.

6.4. Reference to other sections Information regarding safe handling – see section 7.

Information regarding personal protective equipment – see

section 8.

Information regarding disposal – see section 13.

SECTION 7: Handling and storage.

7.1. Precautions for safe handling

Handling: When handling observe the usual precautionary measures for

chemicals. Do not breathe vapour. Workers should wash hands and face before eating, drinking and smoking. Material contains solid components as filler; mix before use. Do not dilute or mix

with other (paint) products.

Information about fire - and explosion protection: No specific requirements.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep container tightly closed in a cool, well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from direct sunlight Avoid moisture from entering by keeping the containers tightly

closed when not in use.

Requirements to be met by storerooms and receptacles: Preferably keep in the original packaging. Keep

container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Suitable packaging material: Original packaging. Closed, coated tin or plastic can.

Suitable material for tanks and pipelines: Stainless steel, coated steel, polyethylene.

Information about storage in one common storage facility: Keep away from oxidants, strong bases and

acids.

Further information about storage conditions: Recommended storage temperature 1 – 49 °C. Tightly

closed, cool, dry, ventilated.

7.3. Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection.

SAFETY DATA SHEET

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 5/11 Version: 3.2

8.1. Control parameters

No exposure limit value known.

8.2. Exposure controls

Personal protective equipment: Do not smoke, eat or drink whilst working. Wear suitable

protective clothing (preferably cotton).

Mouth and nose protection: Ventilation, general extraction, local exhaust in case of

insufficient ventilation, respiratory protection (e.g. EN149, filter

type A).

Skin and body: Wear appropriate chemical protective clothing (e.g. EN 13034

type PB [6], including shoes or boots, single-use protective

clothing or thick cotton fabric).

Store working clothes separately. Wash hands before breaks

and at the end of work.

Remove immediately all contaminated clothing. Store working

clothes separately. Do not use solvents or thinner.

Hands: Wash hands before breaks and at the end of work. Wear

protective gloves if skin contact may occur (EN 374). Selection of the glove material on consideration of the penetration times,

rates of diffusion and degradation (e.g. nitrile rubber, minimum layer thickness: 0.4 mm, butyl rubber (0.7 mm) or PVC (0.7 mm), for breakthrough time > 480 minutes, level 6). Do not rub

eyes with dirty hands.

Eyes: Safety goggles with side-shields (EN 166). Eye shower.

Environmental exposure controls: Do not disperse product residues into the environment.

SECTION 9: Physical and chemical properties.

9.1. Information on basic physical and chemical properties

General information

Appearance

Form: Liquid.

Colour: Specific colors (black green, pink, lime, signal gray, tomatoes

red).

Odour: Slightly irritant.
Odour threshold: Not determined.
pH-value: 7.9 - 8.1.

Change in condition

Melting point/melting range:
Initial boiling point and boiling range:
Flash Point:

Not determined.
Not determined.
> 100 °C.

Flammability (solid, gas): Not determined. Auto-ignition temperature: Not determined.

Explosive limits

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.
Vapour density: Not determined.



MagPaint Europe B.V. Riezenweg 2

NL - 7071 PR UIft

SAFETY DATA SHEET

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 6/11 Version: 3.2

Relative density: 1.155 - 1.205 (water = 1), depending on colour.

Evaporation rate: Not determined. Solubility in/miscibility with water: Freely soluble. Partition coefficient (n-octanol/water): Not determined.

Viscosity

Dynamic: Not determined.

Kinematic: 90 - 95 KU at 25 °C (Stormer viscometer, ASTM Method D-

562).

Explosive properties: Not determined. Oxidising properties: Not determined.

9.2. Other information

VOC content: No VOC, but about 31 - 35% water.

SECTION 10: Stability and reactivity.

10.1. Reactivity No specific data available.

10.2. Chemical stability Stable under normal conditions.

Thermal decomposition/

Conditions to avoid: No specific data available.

10.3. Possibility of hazardous reactions No specific data available.

10.4. Conditions to avoid Avoid high and low temperatures (loss of quality).

10.5. Incompatible materials
No specific data available.

10.6. Hazardous decomposition

products Unlikely at the recommended storage temperature and under

normal conditions of use. In case of combustion: formation of toxic and corrosive gases/vapours: carbon monoxide, carbon

dioxide, fume.

SECTION 11: Toxicological information.

11.1. Information on toxicological effects

Acute toxicity from the components.

LD/LC50 values relevant for classification:

Product information: CAS#: 55965-84-9 (source supplier)	Mixture of: 5-Chloro-2-methyl-isothiazol-3-one and 2-Methyl-2Hisothiazol-3-one (3:1)	
Oral	LD50	> 5,000 mg/kg (rat)
Inhalation	LC50 (4 h)	0.33 mg/m ³ (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

The following health hazard assessment is based on an assessment of the various ingredients in the product.

Primary irritant effect.



MagPaint Europe B.V. Riezenweg 2

NL - 7071 PR UIft

SAFETY DATA SHEET

Date of issue: 26 February 2018
Trade name: BlackboardPaint

Page: 7/11 Version: 3.2

Effects on the eyes: By mechanical damage (particles): irritation, redness and pain.

Effects on the skin: Not irritating.

Chronic effects: Not classified. Germ cell mutagenicity: Not classified.

Reproductive and

developmental toxicity:

Sensitisation:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Not classified.

Not classified.

Other information: No further relevant information available.

SECTION 12: Ecological information.

12.1. Toxicity

Ecotoxicity from the components.

Aquatic toxicity:

Product information:	Mixture of: 5-Chloro-2-methyl-isothiazol-3-one and 2-Methyl-	
CAS#: 55965-84-9	2Hisothiazol-3-one (3:1)	
(source supplier)		
Fish	LC50 (96 h)	> 0.19 mg/l (oncorhynchus mykiss)
Water flea	EL50 (48 h)	0.16 mg/l (daphnia magna, OECD 202)
Algae	ErC50 (72 h)	0.27 mg/l (selenastrum capricornutum)

The following ecological risk assessment is based on an assessment of the various ingredients in the product.

12.2. Persistence and degradability Contains inorganic components.

12.3. Bioaccumulative potential Significant accumulation in organisms is not to be expected.

12.4. Mobility in soil

The product is (partially) soluble in water.

Further ecological information.

General information: Water hazard class 2 (German regulation) (Self-assessment):

hazardous to water. Do not discharge into groundwater, surface

water or sewage system.

12.5. Results of PBT and

vPvB assessment The product does not meet all of the assessment criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6. Other adverse effects Not dangerous for the ozone layer.

SECTION 13: Disposal considerations.

13.1. Waste treatment methods

Product waste: May be brought to a supervised incineration plant in compliance

with local regulations. The generation of waste should be



PAINT FOR PROS

SAFETY DATA SHEET

Eural code for waste:

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 8/11 Version: 3.2

avoided or minimised wherever possible. If this is not possible, destroy in an approved incineration facility, where flue gases and other toxic combustion products are washed and neutralised. Waste, even small quantities, should never be poured down drains of discharged in surface water.

08 01 12. WASTES FROM THE MANUFACTURE,

FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOÙS ENÁMELS),

ADHESIVES, SEALANTS AND PRINTING INKS, wastes from MFSU of adhesives and sealants (including waterproofing products), wastes from adhesives and sealants containing organic solvents or other dangerous substances. Classified as

hazardous waste.

Depending on branch of industry and production process, also

other EURAL codes may be applicable.

Hazardous waste according to Directive 2008/98/EC.

Uncleaned packaging.

Recommendation: Disposal must be made according to official regulations. Empty

the packaging with care. Do not contaminate soil, water or environment with the waste container. Comply with local regulations with regard to the recovery or disposal of waste.

Eural code for packaging: 20 01 27*. MUNICIPAL WASTES AND SIMILAR

COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES INCLUDING SEPARATELY COLLECTED FRACTIONS, paints, inks, adhesives and resins containing dangerous substances.

Classified as hazardous waste.

SECTION 14: Transport information.

Land transport ADR/RID (cross-border). ADR/GGVSEB class:

Hazard identification number:

UN number:

Packing group:

Label:

Special marking:

-

UN proper shipping name: Tunnel restriction code: -

Note: Not a dangerous good according to the transport regulations.

Inland shipping ADN/ADR.

ADN/R-class: - UN number: -

Environmental hazards: -

Maritime transport IMDG.

IMDG-class: UN number: Label: Packing group: -

PAINT FOR PROS

SAFETY DATA SHEET

Date of issue: 26 February 2018 Trade name: BlackboardPaint

Page: 9/11 Version: 3.2

Maximum quantity: EMS number: Stowage and segregation: Marine pollutant: Proper shipping name: -

Air transport ICAO-TI and IATA-DGR.
ICAO/IATA-class:
UN number:
Label:
Packing group:
Proper shipping name:

14.1. UN number Void.

14.2. UN proper shipping name Void.

14.3. Transport hazard class(es) Void.

14.4. Packing group Void.

14.5. Environmental hazards Void.

14.6. Special precautions for user None.

14.7. Transport in bulk according to Annex II of MARPOL 73/78

and the IBC Code Void.

SECTION 15: Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations:

EU regulations and directives which affect this mixture (not yet directly or indirectly mentioned):

Directive 89/686/EEC Personal protective equipment (is to be replaced from

21 April 2018 by regulation (EU) 2016/425).

Directive 98/24/EC Risks related to chemical agents at work.

Directive 2004/42/EC On the limitation of emissions of volatile organic compounds

due to the use of organic solvents in certain paints and

varnishes.

VOC content: nil /low.

Decision 2010/72/EC Non-inclusion of certain substances as biocides (CAS# 55965-

84-9, product type 7 – film preservatives).

Regulation (EC) 2008/1272 On classification, labelling and packaging of substances and

mixtures.

Regulation (EC) 2009/790 1st ATP of the CLP.

Regulation (EU) 2012/528 Biocides

Regulation (EU) 2015/830 Commission regulation of 28 May 2015 amending Regulation

(EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and

Restriction of Chemicals (REACH).



SAFETY DATA SHEET

Date of issue: 26 February 2018 BlackboardPaint Trade name:

Page: 10/11 Version: 3.2

15.2. Chemical safety assessment A chemical safety assessment has not been carried out.

SECTION 16: Other information.

List of relevant H- and EUH-phrase(s) referred to under

headings 2 and 3: H301 - Toxic if swallowed.

H311 - Toxic in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H331 - Toxic if inhaled.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects. EUH208 - Contains (name of sensitising substance). May

produce an allergic reaction.

Aquatic Acute - Hazardous to the aquatic environment, acute. Aguatic Chronic - Hazardous to the aquatic environment,

chronic.

Acute Tox. - Acute toxicity. Skin Corr. - Skin corrosion. Skin Sens. - Skin sensitization.

Document history: Printed on: 26 February 2018.

> Previous edition: 5.1.2018, version 3.1.

Version: 3.2.

Modification: (Correction, Content (W/W): Section 3).

Information source:

Classification according to Regulation

(EC) No 1272/2008: Classification of the mixture based on the standard calculation

method.

The purpose of this Safety Data The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties. It is the obligation of the user to use this product with care and to act in consideration of the applicable laws and legislation.

Blackboard paint is a trademark of MagPaint Europe B.V..

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous

Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses

par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods IATA:

International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association"

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

Marine Pollutant

SAFETY DATA SHEET

26 February 2018 BlackboardPaint Date of issue: Trade name:

11/11 Page: Version: 3.2

GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
EC50:	Half maximal effective concentration
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
OEL:	Occupational Exposure Limit
NOEC:	No Observed Effect Concentration
vPvB:	Very Persistent and Very Bioaccumulative
PBT	Persistent, Bioaccumulative and Toxic substance
EWC:	European Waste Catalogue
TWA:	Time-Weighted Average, limit value associated with the MAC value
DNEL:	Derived No-Effect Level
DMEL:	Derived Minimal Effect Level
PNEC:	Predicted No-Effect Concentration